

# **Performance Bulletin**





**BOAT MANUFACTURER: FINVAL BOAT MODEL:** 505 FishPro OUTBOARD: VF90LA **TEST DATE:** 16.09.2021

| Finval Boats       |
|--------------------|
| Ukraine            |
| finvalboats.com/en |




#### PERFORMANCE DATA

| PERFORMANCE DATA |       |      |      |
|------------------|-------|------|------|
| RPM              | Knots | L/Nm | Nm/L |
| 700              | 2,7   | 0,4  | 2,2  |
| 1000             | 3,9   | 0,5  | 2,1  |
| 1500             | 4,7   | 0,6  | 1,6  |
| 2000             | 6,9   | 0,6  | 1,6  |
| 2500             | 7,5   | 0,9  | 1,1  |
| 3000             | 9,0   | 1,2  | 0,8  |
| 3500             | 15,1  | 0,8  | 1,3  |
| 4000             | 20,4  | 0,7  | 1,4  |
| 4500             | 23,9  | 0,7  | 1,4  |
| 5000             | 28,6  | 0,7  | 1,3  |
| 5500             | 31,3  | 8,0  | 1,3  |
| 6000             | 34,6  | 1,1  | 0,9  |

Acceleration time in seconds:

| U-25KN | 7,1 5 |
|--------|-------|
| 0-30kn | 9,7 s |



#### FINVAL 505 FishPro

| Length                     | 5,05 | М  |
|----------------------------|------|----|
| Beam                       | 2,10 | М  |
| Dry Weight                 | 675  | Kg |
| Max HP                     | 115  | HP |
| Fuel Capacity              | 88   | L  |
| Weight as Tested (approx.) | 950  | Kg |

### VF90LA

| Horsepower          | 90 Hp           | 66                        | Kw   |  |
|---------------------|-----------------|---------------------------|------|--|
| Type & Displacement | EFI             | 1832                      | cc   |  |
| Configuration       | 4 In-line, 16-v | 4 In-line, 16-valve, SOHC |      |  |
| Weight              |                 | 162                       | Kg   |  |
| Gear Ratio          |                 |                           | 2,33 |  |
| Mounting Position   | 10 mm           | /                         | #1   |  |

## **PROPELLER**

| Series           | Aluminium Talon GP |
|------------------|--------------------|
| Diameter / Pitch | 13 1/8 x 17        |
| Partnumber       | 6FP-45947-00       |

## **TEST CONDITIONS**

| Crew                          |             | 3  | prs. |
|-------------------------------|-------------|----|------|
| Air Temperature               |             | 20 | °C   |
| Wind Speed                    |             | 3  | m/s  |
| Fuel                          |             | 65 | L    |
| Type of water and temperature | Fresh Water | 16 | °C   |

#### **TEST PERFORMANCE SUMMARY**

| Max Average Speed                     | 35  | kn   |
|---------------------------------------|-----|------|
| Best Cruising Nm/L                    | 1,4 | Nm/l |
| Range (95% fuel capacity & best Nm/L) | 121 | Nm   |

Comment:Tested weigth includes 3/4 tank of fuel, 2 battery, safety and test gear

Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability.

Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase.

Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies.

Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.