

## **Performance Bulletin**





BOAT MANUFACTURER: FINNMASTER BOAT MODEL: HUSKY R6 OUTBOARD: VF150XC

TEST DATE:

9/8/2023

Finnmaster Boats Oy
Finland
www.finnmaster.fi

# **FINNMASTER**

#### FINNMASTER HUSKY R6

Length	6.00	М
Beam	2.30	М
Dry Weight	890	Kg
Max HP	150	HP
Fuel Capacity	102	L
Weight as Tested (approx.)	1384	Kg

### VF150XC

5.3 s 7.5 s

Horsepower	150 Hp	110	Kw
Type & Displacement	EFI	2785	сс
Configuration	4 in-line, 16-	valve, D	онс
Weight		224	Kg
Gear Ratio			2.00
Mounting Position		/	#3

### PROPELLER

S	eries		Rel	iance
Ĺ	Diameter / Pitch	13 3/4	х	19
F	Partnumber	68F-4	15974-	20-00

## **TEST CONDITIONS**

Crew		2	prs.
Air Temperature		17	°C
Wind Speed		1	m/s
Fuel		102	L
Type of water and temperature	Salt Water	15	°C

#### **TEST PERFORMANCE SUMMARY**

Max Average Speed	44	kn
Best Cruising Nm/L	1.4	Nm/l
Range (95% fuel capacity & best Nm/L)	140	Nm

Comment:Tested weigth includes full tank of fuel. 1 battery, safety and test gear

Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data opti-leging combination with your dealer prior to purchase. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain the restore of the prevent of th

Trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

© 2021 Yamaha Motor Europe NV. All rights reserved.

RPM	Knots	L/Nm	Nm/L
700	2.9	0.8	1.2
1000	3.9	0.8	1.3
1500	5.5	0.9	1.1
2000	6.5	1.2	0.9
2500	8.8	1.3	0.7
3000	18.0	0.7	1.4
3500	23.9	0.7	1.4
4000	27.9	0.8	1.2
4500	32.6	0.9	1.2
5000	37.2	1.0	1.0
5500	40.6	1.1	0.9
6000	44	1.3	0.8

**PERFORMANCE DATA** 

Acceleration time in seconds: 0-30kn

